

LKV424 Specification	
Items	Description
HDMI version	HDMI2.0 (HDR, YUV4:4:4)
	Compatible with HDCP2.2,HDCP1.4
HDMI interface	4 HDMI input, 4 HDMI output
Transmission rate	18Gbps
Bandwidth	600MHz
Resolution	480i@60Hz、480p@60Hz、576i@50Hz、576p@50Hz、720p@50/60Hz、1080i@50/60Hz、1080p@50/60Hz、3840×2160@24/25/30/60Hz、4096×2160@24/25/30/60Hz
Audio format	LPCM/DTS-HD/DTS-Audio/Dolby Digital plus/Dolby TrueHD 7.1/Dolby Digital 7.1CH/Dolby Atmos
RS-232	3 Pin(GND/Rx/Tx), Baud rate 9600
EDID setting	EDID DIP switch (16 gears)
IR frequency	20KHz~60KHz
Voltage	DC5V/1A
Power consumption	<4W
Working temperature	-20℃~60℃
Storage temperature	-30℃~70℃
Humidity	0~90%RH
Housing	Iron
Color	Black
Weight	375g
Dimensions	210.0(L) x 80.0(W) x 21.0(H) mm
Protection	ESD protection 1a Contact discharge level 2 (±4KV) 1b Air discharge level 3 (±8KV) Implementation of the standard: IEC61000-4-2
	Lightning protection, Surge protection